



لیست قیمت محصولات TVI/CVI کلارنت خرداد ماه ۱۴۰۵

فیدار پردازش
خاورمیانه

مرکز عرضه برترین برندهای حفاظت الکترونیک



CCP-MD6230FN-WCA

2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Sunny LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
Support Audio in TVI & CVI Mode
(Compatible With Dahua Recorder)

25.600.000



CCP-MD6230F-WCA

2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Power LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
Support Audio in TVI & CVI Mode
(Compatible With Dahua Recorder)

25.600.000



NEW

CCP-MD6530CN-WA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Power LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC

32.900.000



CCP-MD6230CN-WCA

2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Power LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
Support Audio in TVI & CVI Mode
(Compatible With Dahua Recorder)

25.600.000



CCP-MD6230B-WCA

2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
2 Power LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
Support Audio in TVI & CVI Mode
(Compatible With Dahua Recorder)

25.600.000



CCP-MD6230E-WCA

2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
Support Audio in TVI & CVI Mode
(Compatible With Dahua Recorder)
IP67, Metal Ball, Easy Installation

33.700.000





CCP-MD6530E-WA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP67, Metal Ball, Easy Installation

41.900.000



CCP-MD6230D-DCA

2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
Support Audio in TVI & CVI Mode
(Compatible With Dahua Recorder)
IP67, Metal Ball, Easy Installation

35.000.000



CCP-MD6230D-WCA

2.0 Megapixel HDTVI Camera
1/2.9" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
Support Audio in TVI & CVI Mode
(Compatible With Dahua Recorder)
IP67, Metal Ball, Easy Installation

33.700.000



CCP-MD6530D-DA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP67, Metal Ball, Easy Installation

43.400.000



CCP-MD6530D-WA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
2.8mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP67, Metal Ball, Easy Installation

41.900.000



Dual Light



CCP-SB6230G-D

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

32.900.000

FULL COLOR



CCP-SB6230G-W

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

31.800.000

Dual Light



CCP-SB6530G-DA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 Dual EXIR LED
30m Warmlight, 40m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

43.100.000

FULL COLOR



CCP-SB6530G-WA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

42.000.000

FULL COLOR



CCP-MB6240X-W

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 EXIR LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

30.900.000

FULL COLOR



CCP-MB6540X-WA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 EXIR LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

41.100.000



فیدار پردازش خاورمیانه

۰۲۱۶۲۹۹۹۰۲۱

Dual Light



NEW

CCP-MB6540N-DA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Dual EXIR LED
40m Warmlight, 60m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

44.700.000

FULL COLOR



CCP-SB6240M-W

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Sunny LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

30.600.000

FULL COLOR



CCP-SB6540M-WA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Sunny LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

40.700.000

FULL COLOR



CCP-MB6240Y-W

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Power LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

30.200.000

FULL COLOR



CCP-MB6540Y-WA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Power LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

36.700.000

Dual Light



CCP-LB6550Z-DA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Power Dual EXIR LED
50m Warmlight, 60m IR Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

48.000.000



CCP-LB6550Z-WA

5.0 Megapixel HDTVI Camera
1/2.8" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
2560(H) × 1920(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Power EXIR LED
50m Warmlight Length
OSD Menu by UTC (output 4-in-1)
Built in MIC
IP66, Metal Case, Easy Installation

46.800.000



CCP-SB6230JN-W

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm F1.2 Starlight Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
3 EXIR LED
30m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Metal Case, Easy Installation

30.400.000



CCP-MB6240PN-WL

2.0 Megapixel Camera
1/2.9" Starlight CMOS Sensor
3.6mm Fixed Lens
1920(H) × 1080(V) Resolution
DWDR, 3DNR, AWB, BLC
4 Power LED
40m Warmlight Length
OSD Menu by UTC (output 4-in-1)
IP66, Plastic (Makrolon) Case
Easy Installation

24.800.000



SMD 




CXP-5604-ZN1

104.500.000

4CH H.265 **5MP-Lite** XVR
 4CH Camera + 1CH IP Camera
 Preview : 4*(5MP-Lite@20)fps
 Record : 4*(5MP-Lite@12/4MP-Lite@17/1080P@15/1080P-Lite@25)fps
 4CH Playback
 Support 4CH SMD, 4CH Perimeter/Tripwire
 Support Face Detection 1CH (Special Firmware, Not At The Same Time As SMD)
 Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
 Pentabrid (Analoge,AHD,CVI,TVI,IP)
 HDMI 1080P & VGA Video Simultaneous Output
 1 SATA HDD Up to 10TB
 1/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
 P2P support, Onvif
 IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD 



CXP-7604-ZN1/4KL


141.100.000

4CH H.265 **Real 5MP** XVR
 4CH Camera (Analog & IP)
 Preview : 4*(5MP@12)fps
 Record : 4*(5MP@12/4MP@15/1080P@25)fps
 4CH Playback
 Support SMD (Human/Vehicle Clasification For 4CH)
 Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
 Pentabrid (Analoge,AHD,CVI,TVI,IP)
 HDMI 4K & VGA Video Simultaneous Output
 1 SATA HDD Up to 10TB
 4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
 P2P support, Onvif
 IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD 



HISILICON
 NEW AI Chipset



CXP-7604-ZHN1/4KL

144.500.000

4CH H.265 **4K-Lite & Real 5MP** XVR
 4CH Camera + 2CH IP Camera
 Preview : 4*(8MP-Lite@15/5MP@12)fps
 Record : 4*(8MP-Lite@15/5MP@12/4MP@16/1080P@25)fps
 4CH Playback (2CH@15fps + 2CH@1fps)
 Support 4CH SMD, 4CH Perimeter/Tripwire
 Support Face Detection
 Support LPD
 Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
 Pentabrid (Analoge,AHD,CVI,TVI,IP)
 HDMI 4K & VGA Video Simultaneous Output, Analog Video Output (BNC)
 1 SATA HDD Up to 10TB
 4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface, RS-485 Port
 P2P support, Onvif
 IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD 



New Ultra Model



CXP-5608-ZU1

132.300.000

8CH H.265 **5MP-Lite** XVR
 8CH Camera + 2CH IP Camera
 Preview : 8*(5MP-Lite@12)fps
 Record : 8*(5MP-Lite@12/1080P-Lite@25)fps
 8CH Playback
 Support 8CH SMD, 8CH Perimeter/Tripwire
 Support Face Detection
 Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
 Pentabrid (Analoge,AHD,CVI,TVI,IP)
 HDMI & VGA Video Simultaneous Output
 1 SATA HDD Up to 10TB
 1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
 P2P support, Onvif
 IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD 



HISILICON
 NEW AI Chipset




CXP-5708-ZHN1

142.900.000

8CH H.265 **5MP-Lite** XVR
 8CH Camera + 4CH IP Camera
 Preview : 8*(5MP-Lite@20)fps
 Record : 8*(5MP-Lite@12/1080P@15)fps
 8CH Playback (4CH@12fps + 4CH@1fps)
 Support 8CH SMD, 4CH Perimeter/Tripwire
 Support Face Detection
 Support LPD
 Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
 Pentabrid (Analoge,AHD,CVI,TVI,IP)
 HDMI & VGA Video Simultaneous Output, Analog Video Output (BNC)
 1 SATA HDD Up to 10TB
 4/1 CH Audio In/Out, 2*USB - 1*10/100 Mbps LAN Interface, RS-485 Port
 P2P support, Onvif
 IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD 



CXP-7608-ZN1/4KL

208.200.000

8CH H.265 **4K-Lite & Real 5MP** XVR
 8CH Camera (Analog & IP)
 Preview : 8*(4K-Lite@15/5MP@12)fps
 Record : 8*(4K-Lite@9/5MP@8/4MP@10/1080P@20)fps
 8CH Playback
 Support SMD (Human/Vehicle Clasification For 8CH)
 Support Face Detection (Special Firmware, Not At The Same Time As SMD)
 Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
 Pentabrid (Analoge,AHD,CVI,TVI,IP)
 HDMI 4K & VGA Video Simultaneous Output
 1 SATA HDD Up to 10TB (Change Adaptur to 12V/5A)
 4/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
 P2P support, Onvif
 IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers



فیدار پردازش خاورمیانه

۰۲۱۶۲۹۹۹۰۲۱

SMD  

HISILICON
NEW AI Chipset




CXP-7608-ZHN1/4KL

212.400.000

8CH H.265 **4K-Lite & Real 5MP** XVR
8CH Camera + 4CH IP Camera
Preview : 8*(4K-Lite@15/5MP@12)fps
Record : 8*(4K-Lite@9/5MP@8/1080P@20)fps
8CH Playback
Support 8CH SMD, 4CH Perimeter/Tripwire
Support Face Detection
Support LPD
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI 4K & VGA Video Simultaneous Output, Analog Video Output (BNC)
1 SATA HDD Up to 10TB
4/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface, RS-485 Port
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD  




CXP-5616-ZN1

238.700.000

16CH H.265 **5MP-Lite** XVR
16CH Camera + 4CH IP Camera
Preview : 16*(5MP-Lite@12)fps
Record : 16*(5MP-Lite@6/4MP-Lite@8/1080P-Lite@16)fps
16CH Playback
Support SMD (Human/Vehicle Clasification For 16CH)
Support Face Detection (Special Firmware, Not At The Same Time As SMD)
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD  

HISILICON
NEW AI Chipset



CXP-5716-ZHN1

246.000.000

16CH H.265 **5MP-Lite** XVR
16CH Camera + 4CH IP Camera
Preview : 16*(5MP-Lite@12)fps
Record : 16*(5MP-Lite@6/4MP-Lite@8/1080P-Lite@16)fps
16CH Playback
Support 16CH SMD, 8CH Perimeter/Tripwire
Support Face Detection
Support LPD
Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)
Pentabrid (Analoge,AHD,CVI,TVI,IP)
HDMI & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers



HISILICON
NEW AI Chipset



CXP-5716-ZHN1-W

258.800.000

16CH H.265 **5MP-Lite** XVR With **Internal Wi-Fi Board & Antenna**

16CH Camera + 4CH IP Camera

Preview : 16*(5MP-Lite@12)fps

Record : 16*(5MP-Lite@6/4MP-Lite@8/1080P-Lite@16)fps

16CH Playback

Support 16CH SMD, 8CH Perimeter/Tripwire

Support Face Detection

Support LPD

Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)

Pentabrid (Analoge,AHD,CVI,TVI,IP)

HDMI & VGA Video Simultaneous Output

1 SATA HDD Up to 10TB

1/1 CH Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface

P2P support, Onvif

IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers


این دستگاه با دارا بودن برد وای فای داخلی به همراه آنتن بیرونی، امکان اتصال بیسیم به شبکه از

طریق مودم و روتر و انتقال اطلاعات و اینترنت را به کاربر می دهد

NEW



HISILICON
NEW AI Chipset



CXP-7616-ZHN1/4KL

321.500.000

16CH H.265 **4K-Lite & Real 5MP** XVR

16CH Camera + 4CH IP Camera

Preview : 16*(4K-Lite@15/5MP@12)fps

Record : 16*(4K-Lite@9/5MP@8/1080P@20)fps

16CH Playback

Support 16CH SMD, 8CH Perimeter/Tripwire

Support Face Detection

Support LPD

Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)

Pentabrid (Analoge,AHD,CVI,TVI,IP)

HDMI 4K & VGA Video Simultaneous Output

1 SATA HDD Up to 10TB

4/1Ch Audio In/Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface, RS-485 Port

P2P support, Onvif

IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers



HISILICON
NEW AI Chipset



CXP-7632-ZHN2/4KL

682.600.000

32CH H.265 **4K-Lite & Real 5MP** XVR

32CH Camera (Analog & IP)

Preview : 32*(4K-Lite@15/5MP@12)fps

Record : 32*(4K-Lite@7/5MP@6/1080P@15)fps

16CH Playback

Support 16CH SMD, 8CH Perimeter/Tripwire

Support Face Detection

Support LPD

Support AOC In TVI Mode (DAC Technology / Broadcast Quality Audio)

Pentabrid (Analoge,AHD,CVI,TVI,IP)

HDMI 4K & VGA Video Simultaneous Output, Analog Video Output (BNC)

2 SATA HDD Each Up to 10TB

4/1 CH Audio In/Out, 4/1 Alarm In/Out, 2*USB

1*10/100/1000 Mbps LAN Interface, RS-485 Port

P2P support, Onvif

IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers





لیست قیمت محصولات IP کلارنت خرداد ماه ۱۴۰۵

فیدار پردازش
خاورمیانه

مرکز عرضه برترین برندهای حفاظت الکترونیک



CIP-MD62300EPU-WAF-IF

1/2.9" 2.4Megapixel **New** Starlight CMOS Sensor
Main Stream 2.0MP (1920*1080)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

54.700.000



CIP-MD62300EP-WAF-IF

1/2.9" 2.4Megapixel Starlight CMOS Sensor
Main Stream 2.0MP (1920*1080)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

54.700.000



CIP-MD62300DP-WAF-IF

1/2.9" 2.4Megapixel Starlight CMOS Sensor
Main Stream 2.0MP (1920*1080)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

54.700.000



CIP-MD65300DPI-WAF-IF

1/3" 5.0Megapixel Starlight CMOS Sensor
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Integrated PoE (Onboard)
Fara View Mobile Monitoring, VMS Monitoring

68.200.000





CIP-MD65300EP-WAH-IF

1/3" 5.0Megapixel Starlight CMOS Sensor, **HiSilicon Chipset**
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

72.400.000



CIP-MD65300EP-WAF-IF

1/3" 5.0Megapixel Starlight CMOS Sensor
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

72.400.000



CIP-MD65300DP-WAF-IF

1/3" 5.0Megapixel Starlight CMOS Sensor
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

72.400.000



CIP-MD65310EP-WAF-IF

1/2.7" 5.0Megapixel Starlight CMOS Sensor
Pro Series 16:9 Ratio
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

95.500.000





CIP-MD65310DP-WAF-IF

1/2.7" 5.0Megapixel Starlight CMOS Sensor
Pro Series 16:9 Ratio
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
2.8mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

95.500.000





CIP-SB62300GPU-WAF-IF

1/2.9" 2.4Megapixel **New** Starlight CMOS Sensor
Main Stream 2.0MP (1920*1080)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

54.300.000



CIP-SB62300GP-WAF-IF

1/2.9" 2.4Megapixel Starlight CMOS Sensor
Main Stream 2.0MP (1920*1080)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

54.300.000



CIP-SB65300GP-WAH-IF

1/3" 5.0Megapixel Starlight CMOS Sensor, **HiSilicon Chipset**
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

69.800.000



CIP-SB65300GP-WAF-IF

1/3" 5.0Megapixel Starlight CMOS Sensor
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
3 EXIR LED, 30m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

69.800.000



فیدار پردازش خاورمیانه

۰۲۱۶۲۹۹۹۰۲۱



CIP-MB65400KP-WAH-IF

1/3" 5.0Megapixel Starlight CMOS Sensor, **HiSilicon Chipset**
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
4 EXIR LED, 40m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

72.500.000



CIP-MB65400KP-WAF-IF

1/3" 5.0Megapixel Starlight CMOS Sensor
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
4 EXIR LED, 40m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Perimeter, Tripwire
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

72.500.000



CIP-LB65600UP-WAH-IF

1/3" 5.0Megapixel Starlight CMOS Sensor, **HiSilicon Chipset**
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
5 Power EXIR LED, 60m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

86.000.000



CIP-MB65410KP-WAF-IF

1/2.7" 5.0Megapixel Starlight CMOS Sensor
Pro Series 16:9 Ratio, Dual Board (Processor & Sensor)
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
4 Power EXIR LED, 50m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

94.400.000



فیدار پردازش خاورمیانه

۰۲۱۶۲۹۹۹۰۲۱



ZI COLOR



CIP-LB65600UP-WZAF-IF

1/1.8" 5.0Megapixel Super LowLight CMOS Sensor
Dual Board (Processor & Sensor)
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
4.0mm F1.0 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
5 Power EXIR LED, 60m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection)
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

131.700.000



HISILICON



CIP-LB65500ZP-WAH-IF

1/3" 5.0Megapixel Starlight CMOS Sensor, HiSilicon Chipset
Main Stream 5.0MP (2880*1620)@25/30fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
3DNR, HLC, BLC
4 Power EXIR LED, 50m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

82.100.000



CIP-LB68510ZP-WAF-IF

1/2.8" 8.0Megapixel SONY STARVIS IMX415 Sensor
Dual Board (Processor & Sensor)
Main Stream 8.0MP (3840*2160)@20fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
4 Power EXIR LED, 50m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
Licence Plate Detection (LPD With Software Update)
IP67 Metal Case, Easy Installation
12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

146.700.000



CIP-MB68410KP-WAF-IF

1/2.8" 8.0Megapixel SONY STARVIS IMX415 Sensor
Dual Board (Processor & Sensor)
Main Stream 8.0MP (3840*2160)@20fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
4 EXIR LED, 40m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
Licence Plate Detection (LPD With Software Update)
IP67 Metal Case, 12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

137.100.000



فیدار پردازش خاورمیانه

۰۲۱۶۲۹۹۹۰۲۱






NEW

CIP-LB68810ZP-DAF-ZIF

1/2.8" 8.0Megapixel SONY STARVIS IMX415 Sensor
Dual Board (Processor & Sensor)
Main Stream 8.0MP (3840*2160)@20fps
H.265/H.264 Encoding, Dual Stream
2.8~12mm F1.6 Starlight Advanced **Motorized** Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
(6+4) Dual EXIR LED, 80m Warmlight, 90m IR Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
Licence Plate Detection (**LPD in 5MP Resolution**)
IP67 Metal Case, 12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

222.600.000






NEW

CIP-LB68810ZP-DAF-IF16

1/2.8" 8.0Megapixel SONY STARVIS IMX415 Sensor
Dual Board (Processor & Sensor)
Main Stream 8.0MP (3840*2160)@20fps
H.265/H.264 Encoding, Dual Stream
16mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
(6+4) Dual EXIR LED, 80m Warmlight, 90m IR Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
Licence Plate Detection (LPD in 5MP Resolution)
IP67 Metal Case, 12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

165.600.000






CIP-LB68510TP-WAF-IF

1/2.8" 8.0Megapixel SONY STARVIS IMX415 Sensor
Dual Board (Processor & Sensor)
Main Stream 8.0MP (3840*2160)@20fps
H.265/H.264 Encoding, Dual Stream
3.6mm F1.6 Starlight Advanced Fixed Lens
Built in Microphone
120db WDR, 3DNR, HLC, BLC
4 Power EXIR LED, 50m Warmlight Length
Onvif (Compatible with Dahua, Hikvision, Maxron & etc)
Private Protocol With Z Series XVR & NVR
SMD (Human/Vehicle Detection), Face Detection,
Perimeter, Tripwire, Loitering, People Counting
Licence Plate Detection (LPD With Software Update)
IP67 Metal Case, 12VDC, Smart PoE Board
Fara View Mobile Monitoring, VMS Monitoring

146.700.000

SMD




CNP-7810F1-4K

CALL

10CH H.265 4K (8.0MP) NVR
80Mbps Incoming Bandwidth
10Ch Live View, Up to 8.0MP Resolution for Preview & Playback
Decode Capacity : 1*(4K@25fps)
Playback 10CH (Main Stream + Sub Stream)
Ai By Camera (Full Channel SMD, Face Detection, Perimeter, Tripwire)
Digital Audio Support
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1 CH Audio Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD



CNP-8810i1-4K


134.000.000

10CH H.265 4K (8.0MP) NVR
100Mbps Incoming Bandwidth
10Ch Live View, Up to 8.0MP Resolution for Preview & Playback
Decode Capacity : 1*(4K@25fps)
Playback 10CH (Main Stream + Sub Stream)
Ai By Camera (Full Channel LPD, SMD, Perimeter, Tripwire)
Ai By NVR (1Ch Face Recognition, 4Ch SMD, 4Ch Perimeter/Tripwire)
Digital Audio Support
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1 CH Audio Out, 2*USB 2.0, 1*10/100 Mbps LAN Interface
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD



HISILICON
NEW AI Chipset



CNP-8820H1-4K

188.600.000

20Ch H.265 4K (8.0MP) NVR
160Mbps Incoming Bandwidth
20Ch Live View, Up to 8.0MP Resolution for Preview & Playback
Decode Capacity : 2*(4K@25fps)
Playback 16Ch (Main Stream + Sub Stream)
Ai By Camera (Full Channel LPD, SMD, Face Detection, Perimeter, Tripwire)
Ai By NVR (4Ch SMD, 4Ch Face Detection, 4Ch Perimeter/Tripwire)
Digital Audio Support
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1 Ch Audio Out, 3*USB 2.0, 1*10/100/1000 Mbps LAN Interface, RS-485
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers



فیدار پردازش خاورمیانه

۰۲۱۶۲۹۹۹۰۲۱

SMD   




CNP-8820i1-4K

180.000.000

20Ch H.265 4K (8.0MP) NVR
120Mbps Incoming Bandwidth
20Ch Live View, Up to 8.0MP Resolution for Preview & Playback
Decode Capacity : 4*(4K@25fps)
Playback 16Ch (Main Stream + Sub Stream)
Ai By Camera (Full Channel LPD, SMD, Perimeter, Tripwire)
Ai By NVR (1Ch Face Recognition, 4Ch SMD, 4Ch Perimeter/Tripwire)
Digital Audio Support
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1 Ch Audio Out, 3*USB 2.0, 1*10/100/1000 Mbps LAN Interface, RS-485
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

SMD   

HISILICON
NEW AI Chipset



CNP-8832H1-4K

227.700.000

32Ch H.265 4K (8.0MP) NVR
200Mbps Incoming Bandwidth
32Ch Live View, Up to 8.0MP Resolution for Preview & Playback
Decode Capacity : 4*(4K@25fps)
Playback 16Ch (Main Stream + Sub Stream)
Ai By Camera (Full Channel LPD, SMD, Face Detection, Perimeter, Tripwire)
Ai By NVR (8Ch SMD, 4Ch Face Detection, 8Ch Perimeter/Tripwire)
Digital Audio Support
HDMI 4K & VGA Video Simultaneous Output
1 SATA HDD Up to 10TB
1 Ch Audio Out, 3*USB 2.0, 1*10/100/1000 Mbps LAN Interface, RS-485
P2P support, Onvif
IOS-Andriod FARA VIEW App, Adaptive Iran & International Servers

FARA - Z MODEM



FZ4000G

50.300.000

4G/LTE USB Modem
ASR1803S chip platform
Built-in antenna / Plug and Play
FDD-LTE 150Mbps & TDD-LTE 130Mbps Cat4
Compatible With Z Series XVR & NVR
Power : 5~18V/0.5~1A
89.6mm*28.6mm*13mm / 50g

این مودم با دستگاه های سری زد همخوانی کامل داشته و از طریق اتصال یو اس بی، اینترنت پر سرعت را در اختیار کاربر می گذارد. به وسیله این مودم می توان از قابلیت ارسال اس ام اس دستگاه های سری زد استفاده نمود



فیدار پردازش خاورمیانه

۰۲۱۶۲۹۹۹۰۲۱



FARA AI ALARM BOX

38.200.000

3 Output Relay Box
1 Output With 12VDC
1 RJ45 Web Management Interface
Compatible With Z Series XVR
12VDC Input (Without Adaptor)

این محصول به وسیله کابل شبکه به رکوردرهای سری زد متصل شده و با تعریف و پیاده سازی سناریوهای مختلف از طریق رکوردر و منوی خود محصول می توان از قابلیت های تشخیص انسان و خودروی دوربین و رکوردر در جهت فعال سازی خروجی محصول استفاده نمود تا خروجی تجهیزاتی از قبیل آژیر، تلفن کننده فرمان به دزدگیر و سایر تجهیزات فرمان پذیر را فعال کرد و از دوربین ها به عنوان دتکتور محیطی با هوش مصنوعی و دقت بسیار بالا استفاده نمود



فیدار پردازش خاورمیانه

۰۲۱۶۲۹۹۹۰۲۱